

Specification PA-1552-1L

Form Factor and Dimensions (W x D x H)	73.5 x 40 x 620 (mm)
Output Power	5600W
Output Voltage (Main)	54V
Output Voltage (Standby)	N/A
Input Voltage	180-305VAC
Power Factor	0.92 @10% Load ; 0.96 @20% Load 0.98 @50% Load ; 0.99 @100% Load
iTHD	3.5% @100% Load 5% @50% Load 15% @10% Load
Efficiency	80 PLUS® Titanium
Current Sharing Method	Active + Droop
Communications	Modbus



# Conduction Cooled PSU 5600W

## Key Features

- 97.5%+ efficiency
- Cold plate liquid cool
- Holdup time > 20ms
- ITIC compliance

## Benefits

- Fanless power supply
- Secure boot functionality
- Modbus communication
- Current share capability with 10+ PSU in parallel

## Applications



HPC



AI



Liquid Cool

## Dimension Details



For more product information and sales inquiries :

- [www.liteon.com](http://www.liteon.com)
- +886-2-8798-2888
- [CIPS-Sales@liteon.com](mailto:CIPS-Sales@liteon.com)
- 13F, No. 555, Siyuan Rd., Xinzhuang Dist., New Taipei City 242034, Taiwan, R.O.C.



Visit us

Specifications are subject to change without notice.